

# L2 Dual Port EV Charger

## Technical Parameters for Model #AC002

<b>APPEARANCE PARAMETERS</b>	Dimensions	280(l)*400(w)*1630(h) (mm)
	Weight	116.8 lbs (including cable)
	Cable Length	4.2m (external line) and can be customized
	Screen	5-inch LCD touch screen
<b>POWER CHARACTERISTICS</b>	Input Voltage	208 V to 240 V
	Input Frequency	60Hz
	Rated Power	48 A / 11kW*2
	Measurement Accuracy	±0.5%
	Output Voltage	Same input voltage
	Output Current	48 A*2
<b>FEATURE DESIGN</b>	UI	LED, swipe, touch screen
	Standard	Complies to UL2594, UL2231-1, UL1991, UL2331-2
<b>COMMUNICATION</b>	Internet Interface	Ethernet (2.4g Wi-Fi, 3g/4g as optional)
	OCPP	OCPP 1.6j
<b>WORKING ENVIRONMENT</b>	Application Site	Indoor/outdoor
	Working Temperature	-30°C ~ +50°C
	Working Humidity	5% to 95% no coagulation
	Working Latitude	<2000m
	Protection Level	NEMA Type-3
	Cooling Method	Natural air cooling
	Leak Current Detection	CCID 20